Stone Coat Countertops
2612 Kersten Court, Kalamazoo, MI, 49048
Phone: 541-450-1976
Website: www.stonecoatcountertops.com

FLOORING ULTIMATE TOP COAT

TECHNICAL DATA SHEET

Stone Coat Flooring Ultimate Top Coat is a stronger, more durable finish for epoxy surfaces, offering enhanced scratch, stain, and chemical resistance. Its advanced formula provides long-lasting protection and an extended working time for easier application.

We have enhanced the original Stone Coat Countertops Ultimate Top Coat, used in our epoxy countertop system, with a unique blend of urethane and proprietary ingredients, creating the perfect balance for smooth, straightforward application and a flawless, professional finish every time. Once applied, it allows light foot traffic in 18-24 hours and fully cures in 3-5 days.

Available in gloss and matte finishes, Stone Coat Flooring Ultimate Top Coat delivers superior durability and a consistently perfect look.

PRODUCT FEATURES:

- Chemical and Stain-Resistant
- Extremely Scratch-Resistant
- Water Resistant
- Easy to Clean
- 100% Solids–no VOCs
- DIY-Friendly

SIZES AVAILABLE:

- 1.5 Gallon Kit
- Matte or Gloss Finish

Mix Ratio by Weight	100 Resin : 90 Hardener
Mix Ratio by Volume	2 Resin : 1 Hardener
Work Time	35 minutes
Dry Time	4-6 hours
Total Cure Time	3-5 days
Light Foot Traffic	18-24 hours
Coverage	500 sq ft per 1.5 gallon kit

BEFORE USE: Thoroughly read Safety Data Sheets, product labels, and the “SAFETY” section in this Technical Data Sheet.

Revision Date: 2/6/2025

Stone Coat Countertops
2612 Kersten Court, Kalamazoo, MI, 49048
Phone: 541-450-1976
Website: www.stonecoatcountertops.com

BEFORE YOU BEGIN

Work Environment: The ideal working temperature is around 65-75°F in a clean, dry, dust-free environment. Keep air movement to a minimum.

Preparation: To ensure proper adhesion, we suggest scuffing the surface with 220-grit sandpaper. Clean dust off with 91% (or higher) Isopropyl alcohol.

Materials: Be prepared with all necessary materials and tools before beginning your project. These items include (but are not limited to):

- Flooring Ultimate Top Coat kit (Parts A and B)
- Graduated measuring/mixing container(s)
- Clean paint stir stick(s)
- Nitrile gloves
- Spiked epoxy shoes
- Multiple 3/8'' nap microfiber paint rollers
- Roller pan(s)

MIXING, POURING, & APPLYING

Mixing Instructions: Empty the entire 1.5 Gallon Flooring Ultimate Top Coat kit into a clean mixing bucket. Using a paint stick, mix thoroughly for 60-90 seconds. Pour the mixed material into a paint roller pan.

Application Instructions: To apply Flooring Ultimate Top Coat, use a de-linted 3/8" nap microfiber roller. Roll the product onto the floor in even, smooth strokes, making sure to feather the edges to blend any lap lines. As you get close to the edges, switch to a 4-6" mini roller for better precision. For best results, wear spiked shoes so you can walk over the wet coating without leaving marks. Continue rolling from wall to wall, working your way toward the exit to avoid stepping on freshly coated areas. You will have 35 minutes of working time to apply the Ultimate Top Coat.

Pro Tips:

- Avoid over dry rolling. Rolling too much as the coat sets can create a rough, uneven texture.
- Do not worry about faint lap lines—they will disappear as the coating dries.
- Practice first! Test your technique on a sample piece before starting your project.

BEFORE USE: Thoroughly read Safety Data Sheets, product labels, and the "SAFETY" section in this Technical Data Sheet.

Revision Date: 2/6/2025

Stone Coat Countertops
2612 Kersten Court, Kalamazoo, MI, 49048
Phone: 541-450-1976
Website: www.stonecoatcountertops.com

CLEAN UP & DISPOSAL

Clean up: Tools can be cleaned with isopropyl alcohol or a residue-free cleaner. DO NOT use soap and water.

Disposal: Dispose of product and containers according to Federal, State, and local regulations. Store any unused, unmixed product in the original bottles, tightly sealed, and in a cool, dry place. Once mixed, the product cannot be stored and must be used or properly disposed of.

SAFETY

Safety: Before use, thoroughly read Safety Data Sheets and product labels. Follow safety precautions, directions, and wear appropriate personal protective equipment for your use and application.

DISCLAIMER: The information provided herein is believed to be accurate; however, Stone Coat Countertops makes no warranties, express or implied, regarding its accuracy or completeness. It is the sole responsibility of the user to determine the suitability of the product for its intended use. The user assumes all risks and liabilities arising from such use.

BEFORE USE: Thoroughly read Safety Data Sheets, product labels, and the "SAFETY" section in this Technical Data Sheet.

Revision Date: 2/6/2025